

	CHBU / CONCENTRIC UFO HIGH BAY					
	PROJECT :					
	NOTE :					
	COMPANY NAME:					
TYPE:		DATE:				
CATALOG NUMBER:						
ITEM CODE	WATT	CCT&CRI	BEAM ANGLE	VOLTAGE	OPTION	MOUNTING

SPECIFICATION

HIGH PERFORMANCE LED 150LM/W
CONCENTRIC LED ARRAY
LUMEN OUTPUT: > 150LM/W
POWER EFFICIENCY>95%
CCT 4000K / 5000K
CRI: 70RA
WATTAGE: 100W / 150W / 185W
BEAM ANGLE: 60° / 90° / 120° / 70° X 90°
INPUT VOLTAGE 120/277VAC OR 347VAC, 60HZ
OPERATING TEMPERATURE: -40°C TO +65°C
L70-70000HRS
STANDARD POWER CABLE SOW 3/18 AWG
OPTIONAL 0/10V DIMMING CABLE
POWER COAT BLACK
INGRESS PROTECTION IP66
5 YEAR WARRANTY STANDARD



FEATURES

CONSTRUCTION

- High pressure die-cast aluminum housing
- Polyester powder paint finish
- Extrusion aluminium housing for driver components
- Power coat paint finish black
- IP66
- polycarbonate lens
- Operating temperature: -40°C ~ +65°C

MOUNTING

- Standard steel eye loop for suspension

ELECTRICAL

- 120/277 VAC, 347VAC 60HZ
- 0-10V dimming optional
- PF>0.95

COMPLIANCE

- ULc / DLC / IEC
- ICES 005
- ROHS
- IEC60929 Annex E
- Suitable for wet location






MODELS


Item Code	Watts(W)	Lumens (LM/W)*	CCT	Voltage
CHBU-100W-XXK-XXXV	100	> 150LM/W	4000K/5000K	120-277 Or 347
CHBU-150W-XXK-XXXV	150		4000K/5000K	
CHBU-185W-XXK-XXXV	185		4000K/5000K	

DIMENSIONS

Watts(W)	Weight (lbs)	Fixture Dimension (D * D * H) (Inch)
100	8.8	11.8 X 11.8 X 12.2
150	8.8	11.8 X 11.8 X 12.2
185	8.8	11.8 X 11.8 X 12.2



Pole



Hook

OPTIONAL (MUST BE SEPECIFIED)

OPTION	
MS	Motion Sensor
DIM	0/10V dimming